

Data sheet

Part number : VCTW1152GDS-TR



2011/65/EU, (EU)2015/863
10 Substances regulation compliant



Lead-free solder heat resistant product








Package	SMD Top view Package, White color emitting LED Outer dimension 2.2 x 1.7 x 0.75mm (L x W x H)
Product features	<ul style="list-style-type: none"> •Luminous intensity 3,500mcd TYP. •Moisture sensitive level : 2a •Lead-free soldering compatible •RoHS : 2011/65/EU, (EU)2015/863 compliant

Recommended applications

- Light source for automotive use, back light, various indicators, etc.

Outline dimensions

VCTW1152GDS-TR




Marking for traceability

No.	Part name	Material	Qty.
①	LED die	InGaN	1
②	Lamp housing	White resin	1
③	Electrode	Pd/Au plating	Cathode: 2 Anode: 1
④	Encapsulant	Silicone resin	1

Recommended soldering pattern

Unit : mm



Specifications

VCTW1152GDS-TR

【Product overview】

Die material	InGaN
Emitting color	White
Resin color 【Emitting area】	Diffused pale yellow
Resin color 【Lamp housing】	White

【Absolute maximum ratings】

Ta=25°C

Item	Symbol	Maximum ratings	Units
Power dissipation	P_d	130	mW
Forward current	I_F	40	mA
Repetitive peak forward current 【1ms, 1/10 duty】	I_{FRM}	100	mA
I_F derate linearly 【Ta=from 85°C】	ΔI_F	1.14	mA/°C
I_{FRM} derate linearly 【Ta=from 85°C】	ΔI_{FRM}	2.86	mA/°C
Reverse voltage	V_R	5	V
Operating temperature	T_{opr}	-40 to +100	°C
Storage temperature	T_{stg}	-40 to +120	°C
Junction temperature	T_j	120	°C
Electrostatic discharge threshold 【HBM】	ESD	2,000	V
Soldering temperature 【Reflow soldering】	T_{sld}	260	°C

Note1

Note2

Note1 ESD testing method : JEITA ED-4701/302A(304A)/IEC 60810 Human Body Model(HBM) 1.5kΩ,100pF

Note2 Please refer to page 9, soldering conditions.

【Thermal Characteristics】

Ta=25°C

Item	Symbol	Typ.	Units
Thermal resistance 【Junction - Ambient temp.】	$R_{th(j-a)}$	150	°C/W
Thermal resistance 【Junction - Solder point】	$R_{th(j-s)}$	15	°C/W

Note3

Note3 $R_{th(j-a)}$ measurement conditions / Substrate : FR4 (t=1.6mm)
Pattern size : 16mm²

Specifications

VCTW1152GDS-TR

【Electro-optical characteristics】

Ta=25℃

Item	Symbol	Conditions	Min.	Typ.	Max.	Units
Forward voltage	V_F	$I_F = 30\text{mA}$	2.4	2.8	3.2	V
Luminous intensity	I_V	$I_F = 30\text{mA}$	2,200	3,500	4,700	mcd
Chromaticity coordinates	x	$I_F = 30\text{mA}$	-	0.2975	-	
	y		-	0.3028	-	
Half intensity angle	$\Delta\theta_x$	$I_F = 30\text{mA}$	-	115	-	deg.
	$\Delta\theta_y$		-	115	-	

Note4

Note5

Note6,7

Note8

Note4 Tolerance: $\pm 0.1\text{V}$

Note5,6 Please refer to each sorting chart.

Note7 Chromaticity coordinates ; x and y according to CIE1931

Note8 Viewing Angle at 50% I_V , $\Delta\theta_x$; Housing long side axis, $\Delta\theta_y$; Housing short side axis

【Sorting chart for luminous intensity】

LEDs shall be sorted out into the following chart and each rank parts shall be packed separately when shipping.

Rank	Luminous intensity I_V (mcd)		Conditions
	Min.	Max.	
D5	2,200	2,700	$I_F = 30\text{mA}$ $T_a = 25^\circ\text{C}$
D6	2,700	3,300	
D7	3,300	3,900	
D8	3,900	4,700	

Note The above values are the settings of the sorting machine.
Tolerance: $\pm 10\%$


Since the luminous intensity rank depends on the chromaticity rank,
the luminosity 3 rank corresponding to the chromaticity rank is selected.

Specifications

VCTW1152GDS-TR

【Sorting chart for chromaticity coordinates】

LEDs shall be sorted out into the following chart and each rank parts shall be packed separately when shipping.





$I_F=30\text{mA}$, $T_a=25^\circ\text{C}$

	Point1		Point2		Point3		Point4	
Rank	x	y	x	y	x	y	x	y
3C	0.2480	0.2590	0.2600	0.2770	0.2740	0.2680	0.2620	0.2500
4C	0.2600	0.2770	0.2720	0.2950	0.2860	0.2850	0.2740	0.2680
5C	0.2720	0.2950	0.2840	0.3120	0.2970	0.3030	0.2860	0.2850
6C	0.2840	0.3120	0.2950	0.3300	0.3090	0.3200	0.2970	0.3030
7C	0.2950	0.3300	0.3070	0.3470	0.3210	0.3380	0.3090	0.3200
8C	0.3070	0.3470	0.3190	0.3650	0.3330	0.3560	0.3210	0.3380
3D	0.2620	0.2500	0.2740	0.2680	0.2880	0.2580	0.2770	0.2410
4D	0.2740	0.2680	0.2860	0.2850	0.3000	0.2760	0.2880	0.2580
5D	0.2860	0.2850	0.2970	0.3030	0.3110	0.2930	0.3000	0.2760
6D	0.2970	0.3030	0.3090	0.3200	0.3230	0.3110	0.3110	0.2930
7D	0.3090	0.3200	0.3210	0.3380	0.3350	0.3290	0.3230	0.3110
8D	0.3210	0.3380	0.3330	0.3560	0.3470	0.3460	0.3350	0.3290

Note The above values are the settings of the sorting machine.
Tolerance: ± 0.01





Technical Data

VCTW1152GDS-TR







Technical Data

VCTW1152GDS-TR



Technical Data

VCTW1152GDS-TR



Soldering condition


VCTW1152GDS-TR

【Soldering Precaution】

(acc.to JEITA-4701/301A(301D))

1. Heat stress during soldering will influence the reliability of LEDs, however that effect will vary on heating method. Also, if components of varying shape are soldered together, it is recommended to set the soldering pad temperature according to the component most vulnerable to heat (e.g., surface mount LED).
2. LED parts including the resin are not stable immediately after soldering (when they are not at room temperature), any mechanical stress may cause damage to the product. Please avoid such stress after soldering, especially stacking of the boards which may cause the boards to warp and any other types of friction with hard materials.
3. Recommended temperature profile for the reflow soldering is listed as the temperature of the resin surface. Temperature distribution varies on heating method, PCB material, other components in the assembly, and mounting density .
Please do not repeat the heating process in reflow process more than 2 times.

【Recommended reflow soldering condition】



Note 1 Temperature profile for the reflow should be set to the surface temperature of resin which is on the top of LED. This should be the maximum temperature for soldering. Lowering the heating temperature and decreasing heating time is very effective in achieving higher reliability.

Note 2 The reflow soldering process should be done up to 2 times Max. When second process is performed, interval between first and second process should be as short as possible to prevent absorption of moisture to resin of LED. The second soldering process should not be done until LEDs have returned to room temperature (by nature-cooling) after first soldering process.

Soldering condition

VCTW1152GDS-TR

4. If soldering manually, the peak temperature changes according to the size of land and the shape of soldering iron tip. Therefore please confirm there is no problem before usage. Also, Stanley recommends using a soldering iron equipped with temperature control and the peak temperature to be lowered.
During the actual soldering process, make sure that the soldering iron never touches the LED itself, and avoid the LED's electrode temperature reaching above the temperature of the solder pad.
All repairs must be performed only once in the same spot, and please avoid reusing components.
5. In soldering process, immediately after iron tip is cleaned, please make sure that the soldering iron reaches the appropriate temperature, then use it. Also, please avoid applying any types of pressure to the soldered components before the solder is cooling and hardening, as it may deteriorate solder performance and solder quality.

【Recommended manual soldering condition】

Temperature of iron tip	350°C max.
Soldering duration, time	3sec. max., 1 time

6. When using adhesive material for tentative fixatives, thermosetting resin or Ultraviolet radiation(UV) setting resin with heat shall be recommended.
The curing condition, Temperature:150°C max. / Time:120sec.max.
7. Flow soldering (dip soldering) is not guaranteed for this product.
8. Please confirm in advance there is no problem by assessment on your side if cleaning process is necessary.
We can not accept any quality issues caused by the cleaning process.
As this product uses the low hardness silicone resin for the lens, please avoid cleaning to give pressure on the surface of the resin.
Please make sure ultrasonic cleaning is not recommended for this product as well.
We will recommend isopropyl alcohol as a solvent used for cleaning.
Some chemicals, including Freon substitute detergent could corrode the lens or the casing surface, which cause discoloration, cloud, crack and so on.
Please review the reference chart below for cleaning. If water is used to clean (including the final cleaning process), please use pure water (not tap water), and completely dry the component before using.

Cleaning agents	Recommended / Not recommended
Isopropyl Alcohol	✓ Recommended
Trichloroethylene	x Not recommended
Chloroethene	x Not recommended
Acetone	x Not recommended
Thinner	x Not recommended

Handling precautions

VCTW1152GDS-TR

【For Electric Static Discharge (ESD)】

InGaN die LEDs are sensitive to voltage surges generated by On/Off status change and friction with synthetic materials, which may cause severe damage to the die or undermine its reliability.

Damaged products may experience conditions such as extremely high reverse voltage or decrease of forward rise voltage deteriorating their optical characteristic.

Stanley InGaN products are packed with anti-static components.

However, the following precautions must be taken into account upon product shipment.

1. Electrification / static electricity protection

In order to avoid product (die) damage from static electricity caused by electrified operator and other materials electrified friction coming in contact with the product, Stanley recommends taking the following precautions.

- ① Do not place electrified non-conductive materials near the LED product.
Avoid LED products from coming into contact with metallic materials.(Should the metallic material be electrified , the sudden surge voltage will most likely damage the product.)
- ② Avoid a working process which may cause the LED product to rub against other materials.
- ③ Install ground wires for any equipment, where they can be installed, with measures to avoid static electricity surges.
- ④ Prepare a ESD protective area by placing a Conductive Mattress (1MΩ MAX.) and Ionizer to remove any static electricity.
- ⑤ Operators should wear a protective wrist-strap.
- ⑥ Operators should wear conductive work-clothes and shoes.
- ⑦ To handle the products directly, Stanley recommends the use of ceramic, and not metallic, tweezers.

2. Working environment

- ① Dry environment is more likely to cause static electricity. Although a dry environment is ideal for storage state of LED products, Stanley recommends an environment with approximately 50% humidity after the soldering process.
- ② Recommended static electricity level in the working environment is less than 150V, which is the same value as Integrated Circuits (which are sensitive to static electricity).

Handling precautions

VCTW1152GDS-TR

【Other precautions】


1. The products are designed to achieve higher performance reliability, however, they can be influenced by usage conditions.
2. Absolute maximum ratings are set to prevent LED products from breaking due to extreme stress (temperature, current, voltage, etc.). These ratings must never be overrun even for a moment.
3. To achieve the highest performance reliability, it is necessary to take into account, factors such as forward voltage adjusted to the usage temperature condition, derating of the power consumption, and other variable factors.
4. Please insert straight protective resistors into the circuit in order to stabilize LED operation and to prevent the device from overheating.
5. Please avoid to stick foreign materials because molding resin in the products has adhesiveness.
And please don't touch lens portion, so it cause the wire open circuit etc. when the stress hangs to the lens portion.
6. To handle with tweezers, please avoid excessive stress to this part. Excessive stress may cause non-lighting due to deformation, crack and breaking. Stanley recommends the use of ceramic tweezers, and not sharp one.
7. Please note external stress such as dropping and hitting may cause non-lighting due to deformation, crack and breaking.
8. Stanley does not recommend supersonic wave welding as it cause resonance with sealing resin and may cause breaking of conductive wire.
Please use after affirming beforehand there is no problem.
9. The solder crack by the heat stress might be generated when the LED is soldered with the metal plate and go enough in a prior confirmation, please.
10. Please note piling PCBs may stress LEDs. It may cause non-lighting due to deformation, crack and breaking.
11. This part does not have proof for water, humidity and salt damage.
Please use after affirming beforehand there is no problem if using on above conditions.
12. Please keep in desiccator regardless of before or after mounting not to be affected by corrosive gas when keeping products.
Also please make sure if there is any gas which occur in surrounding area or enter from outside when using products.
13. Please check the actual performance in the assembly because the Specification Sheets are described for single LED.
14. Please refrain from looking directly at the light source of LED at high output, as it may harm your vision.
15. The products are designed to perform without failure in the recommended usage conditions.
However, please take the necessary precautions to prevent fire, injury, and other damages from these unexpected failures.
16. The products are manufactured to be used for ordinary electronic equipment. Please contact our sales staff in advance when exceptional quality and reliability are required, when the failure or malfunction of the products might directly jeopardize life or health (such as for airplanes, aerospace, transport equipment, medical applications, nuclear reactor control systems and so on).
17. The formal specification sheets should be exchanged and signed by both parties.

Handling precautions


VCTW1152GDS-TR

【Handling precautions for product mounting】

<Recommendation>


1. Picking up point with nozzle : Lamp housing of the product ( area : Shown below)

The pick up point is lamp housing only because the silicone resin used for the lens is soft.
(If the nozzle makes contact with the lens, the products might be destroyed)



Please adjust the load, the pick up point, the nozzle diameter and etc. before mounting because the over load can cause the breakage of the lamp housing.

2. Recommended nozzle shape





Handling precautions

VCTW1152GDS-TR

【Other precautions for product mounting】

1. Regarding exposed metal

This LED has exposed metal on the non soldering area. Please avoid touching electro conductive material on this exposed metal as it may connect with other electrode and short out.




2. Terminal mounting section


There are 3 terminals on the back.

It becomes 3 terminals mounting for the soldering, and mounting on following symmetry pad is also possible.

Provided that, please confirm there is no problem in your company before usage.



Symmetrical pad



Recommended metal mask for symmetrical pads

Packaging specifications

VCTW1152GDS-TR

This product is baked (moisture removal) before packaging, and is shipped in moisture-proof packaging (as shown below) to minimize moisture absorption during shipping. However, in regard to storing the products, the use of dry-box under the following conditions is recommended. Moisture-proof bag as the packaging is made of anti-static material but packaging box is not.

【Recommended storage condition / products warranty period】

Temperature	+5 to 30°C
Humidity	Under 70%

In the case of the package unopened, please use within **6 months under 【Recommended storage condition】**. Please avoid rapid transition from low temp. condition to high temp. condition and storage in corroding and dusty environment.

【Time elapsed after package opening】

The package should not be opened until immediately prior to its use, and please keep the time frame between package opening and soldering which is **【maximum 672h】**.

If the device needs to be soldered twice, both soldering operations must be completed within the 672h.

If any components should remain after their use, please reseal the package and store them under the conditions described in the **【 Recommended storage condition 】**.

This product must be required to perform baking process (moisture removal) for **at least 48h and not exceed for 72h, at 60+ / -5 degrees Celsius** if following conditions apply.

1. In the case of color of indicators (those are in the package of desiccant) change or lose its blue color.
2. In the case of time is passed for 672h after the package is opened once.


Baking process should be performed after putting out from package.

Baking may be performed in the tape-reel form, however if it is performed with the reel stacked over one another, it may cause deformation of the reels and taping materials, which may cause problems during production. Please make sure that the product has cooled to normal temperature after performing the baking process. Provided that, baking process shall be 2 times max.

Packaging specifications


VCTW1152GDS-TR

【Moisture-proof packaging specification】



No.	Part name	Material	Remarks
①	Moisture-proof bag with aluminum layer	PET+Al+PE	with ESD protection

【Flow chart-package opening to mounting】



Allowable leaving time means the maximum allowable leaving time after opening package, which depends on each LED type.

The allowable leaving time should be calculated form the first opening of package to the time when soldering process is finished.

When judging if the allowable leaving time has exceeded or not, please subtract the soldering time. The allowable leaving time after reopening should be calculated form the first opening of package, or from the time when baking process is finished.

Packaging specifications


VCTW1152GDS-TR

【 Packing box 】

(RoHS / ELV compliant)

Box type	Outline dimension L × W × H (mm)	Capacity of the box
Type A	280 × 265 × 45	3 reels
Type B	310 × 235 × 265	15 reels
Type C	440 × 310 × 265	30 reels
Type D	305 × 270 × 65	3 reels
Type E	370 × 280 × 270	30 reels
Type F	530 × 380 × 270	60 reels

The above measurements are reference values.
The box is selected out of the above table by shipping quantity.



No.	Part name	Material	Remarks
②	Packing box	Corrugated Cardboard	without ESD protection

Packaging specifications

VCTW1152GDS-TR

【Label specification】

(acc.to JIS-X0503(Code-39))

A Product label

STANLEY-STANLEY ELECTRIC CO.,LTD.-

A

B

(C)

D PCS

E

Lot No. F

G

- A. Parts number
- B. Bar-code for parts number
- C. Parts code (In-house identification code for each parts number)
- D. Packed parts quantity
- E. Bar-Code for packed parts quantity
- F. Lot number & rank
- (Please refer to lot number notational system for details)
- G. Bar-code for lot number & rank

B Opto device label

STANLEY OPTO DEVICES

A

御中

B

D

(C)

Q'TY E PCS G

C/NO F

H

STANLEY ELECTRIC CO.,LTD.

- A. Customer name
- B. Parts type
- C. Parts code
- D. Parts number
- E. Packed parts quantity
- F. Carton number
- G. Shipping date
- H. Bar-code for In-house identification number


<Remarks> Bar-code font : acc.to Code-39(JIS-X0503)

Taping and reel specifications

VCTW1152GDS-TR

(acc.to JIS-C0806-03)

【Appearance】



Note
"-TR" means Cathode Side of LEDs; should be placed on the sprocket-hole side.

Items		Specifications	Remarks
Leader area	Cover-tape	Cover-tape shall be longer than 300mm without carrier-tape	The end of cover-tape shall be held with adhesive tape.
	Carrier-tape	Empty pocket shall be more than 25 pieces .	Please refer to the above figure for Taping & reel orientation .
Trailer area		Empty pocket shall be more than 40 pieces .	The end of taping shall be inserted into a slit of the hub.

Taping and reel specifications

VCTW1152GDS-TR

【 Qty. per reel】

3,000parts/reel

Minimum Qty. per reel might be 500 parts when getting less than 3,000 parts.

In such case, parts of 500-unit-qty. shall be packed in a reel and the qty. shall be identified on the label

【Mechanical strength】

Cover-tape adhesive strength shall be 0.1 ~ 1.0N (An angle between carrier-tape and cover-tape shall be 170 deg.).

Both tapes shall be so sealed that the contained parts will not come out from the tape when it is bent at a radius of 15mm.

【 Others】

Reversed-orientation, Up-side down placing, side placing and out of spec. parts mix shall not be held.

Empty pocket per reel shall be defined as follows.


Qty./reel	Max. qty. of empty pocket	Remarks
500	1	-
1,000	1	-
1,500	1	-
2,000	2	No continuance
2,500	2	No continuance
3,000	3	No continuance

Taping and reel specifications
(acc.to JIS-C0806-03)


VCTW1152GDS-TR

Unit: mm

【Taping dimensions】



【Reel dimensions】



No.	Part name	Remarks
①	Carrier-reel	with ESD protection
②	Carrier-tape	with ESD protection
③	Cover-tape	with ESD protection

Lot number notational system

VCTW1152GDS-TR

①	②	③	④	⑤	⑥	⑦	⑧	⑨							

① - 1digit : Production location (mark identify alphabet)

② - 1digit : Production year (The last digit of production year 2025→5, 2026→6, 2027→7, 2028→8 ...)

③ - 2digits : Production month (Jan. to Sep. , should be 01,02,03 ...)

④ - 2digits : Production date

⑤ - 3digits : Serial number

⑥ - 2digits : Tape and reel following number

⑦ - 2digits : Total power rank.

(If total power rank is 1 digit, "-" shall be dashed on the place for the second digit.

If there is no identified rank, "-" is used to indicate.)

⑧ - 2digits : Color / chromaticity rank

(If color / chromaticity rank is 1 digit, "-" shall be dashed on the place for the second digit.

If there is no identified intensity rank, "-" is used to indicate.)

⑨ - 1digit : VF rank (If rank is not defined, "-" is described.)

Compliance with RoHS / ELV

VCTW1152GDS-TR

This product is in compliance with RoHS / ELV.

Prohibition substance and it's criteria value of RoHS / ELV are as follows.

- RoHS instruction ... Refer to following 1 to 10.
- ELV instruction ... Refer to following 1 to 4.

2011/65/EU, (EU)2015/863

No.	Substance group name	Maximum permissible concentration value
1	Lead and its compounds	1,000ppm (0.1%)
2	Cadmium and its compounds	100ppm (0.01%)
3	Mercury and its compounds	1,000ppm (0.1%)
4	Hexavalent chromium compounds	1,000ppm (0.1%)
5	PBB : Polybrominated Biphenyls	1,000ppm (0.1%)
6	PBDE : Polybrominated Biphenyl Ethers	1,000ppm (0.1%)
7	DEHP : Bis (2-ethylhexyl) phthalate	1,000ppm (0.1%)
8	BBP : Butyl benzyl phthalate	1,000ppm (0.1%)
9	DBP : Dibutyl phthalate	1,000ppm (0.1%)
10	DIBP : Diisobutyl phthalate	1,000ppm (0.1%)

Reliability Testing Result

VCTW1152GDS-TR

1. Reliability testing result

Test item	Standard	Test condition	Duration	Failure
Room temperature operating life	JEITA ED-4912A	Ta=25°C I _F =40mA	1,000h	0 / 20
High temperature operating life	JEITA ED-4701 / 100A(101A)	Ta=85°C I _F =40mA	1,000h	0 / 20
Low temperature operating life	JIS C60068-2-1	Ta=-40°C I _F =40mA	1,000h	0 / 20
High wet – High temperature operating life	JEITA ED-4701 / 100A(102A)	Ta=85°C Rh=85% I _F =40mA	1,000h	0 / 20
High temperature storage life	JEITA ED-4701 / 200A(201A)	Ta=120°C	1,000h	0 / 20
Low temperature storage life	JEITA ED-4701 / 200A(202A)	Ta=-40°C	1,000h	0 / 20
Wet high temperature storage life	JEITA ED-4701 / 100A(103A)	Ta=85°C Rh=85%	1,000h	0 / 20
Thermal shock	JEIAJ ED-4701 / 100A(105A)	Ta=-40°C to 120°C (each 15min)	1,000 cycles	0 / 20
Thermal shock operating	JEITA ED-4701 / 100A(105A)	Ta=-40°C(OFF) to 85°C(I _F =40mA ON) (each 15min)	1,000 cycles	0 / 20
Cycled temperature humidity operating life	EIAJ ED-4701 / 200(203)	Ta=-30°C to 80°C 95% 8h / cycle I _F =40mA 5min on-off	30 cycles	0 / 20
Resistance to reflow soldering	JEITA ED-4701 / 301A(301D)	Moisture Soak : 60°C 60% 120h Preheating : 150 to 180°C 90-120sec Soldering : 260°C peak	2 times	0 / 20
Electrostatic discharge (ESD)	JEITA ED-4701 / 302(304A)	C=100pF R2=1.5kΩ ±2,000V	3 times of each polarity	0 / 20

2. Failure criteria

Item	Symbol	Condition	Failure criteria
Luminous intensity	I _V	I _F =30mA	Testing Min. Value < Standard Min. Value × 0.5
Forward voltage	V _F	I _F =30mA	Testing Max. Value ≥ Standard Max. Value × 1.2
Cosmetic appearance	-	-	Notable discoloration, deformation and cracking

Special Notice to Customers Using the Products and Technical Information Shown in This Data Sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products that have been described to this catalog are manufactured so that they will be used for the electrical instrument of the benchmark (OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument).
The application of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. needs a high reliability and safety, and the breakdown and the wrong operation might influence the life or the human body. Please consult us beforehand if you plan to use our product for the usages of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. except OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument.
- 5) In order to export the products or technologies described in this data sheet which are under the “Foreign Exchange and Foreign Trade Control Law,” it is necessary to first obtain an export permit from the Japanese government.
- 6) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 7) The most updated edition of this data sheet can be obtained from the address below:
<http://www.stanley-components.com/en/>