

# Data sheet

Part number : VXKW1154LCS-TR



Package	PLCC-2 package, Pale blue green color emitting LED Outer dimension 3.5 x 2.8 x 1.9mm ( L x W x H )
Product features	<ul style="list-style-type: none"> <li>•Moisture sensitive level : 2a</li> <li>•Lead-free soldering compatible</li> <li>•RoHS2 compliant</li> </ul>


## Recommended applications

- Lighting for automotive interiors, cluster meters, various switches, other indicator light sources, etc.

Outline dimensions


VXKW1154LCS-TR

Unit : mm  
Weight : 33mg  
Tolerance : ±0.2



Recommended soldering pattern

Unit : mm



## Specifications

VXKW1154LCS-TR

## 【Product overview】

Die material	InGaN
Emitting color	Pale blue green
Resin color 【Emitting area】	Diffused pale green
Resin color 【Lamp housing】	White

## 【Absolute maximum ratings】

Ta=25°C

Item	Symbol	Maximum ratings	Units
Power dissipation	$P_d$	140	mW
Forward current	$I_F$	40	mA
Repetitive peak forward current 【1ms, 1/10 duty】	$I_{FRM}$	100	mA
$I_F$ derate linearly 【Ta=from 85°C】	$\Delta I_F$	1.14	mA/°C
$I_{FRM}$ derate linearly 【Ta=from 85°C】	$\Delta I_{FRM}$	2.86	mA/°C
Reverse voltage	$V_R$	5	V
Operating temperature	$T_{opr}$	-40 ~ +100	°C
Storage temperature	$T_{stg}$	-40 ~ +120	°C
Junction temperature	$T_j$	120	°C
Electrostatic discharge threshold 【HBM】	ESD	1,000	V
Soldering temperature 【Reflow soldering】	$T_{sld}$	260	°C

Note1

Note2

Note1 ESD testing method : JEITA ED-4701/302A(304A)／IEC 60810 Human Body Model(HBM) 1.5kΩ,100pF

Note2 Please refer to page 9, soldering conditions.

## 【Thermal Characteristics】

Ta=25°C

Item	Symbol	Typ.	Units
Thermal resistance 【Junction - Ambient temp.】	$R_{th(j-a)}$	220	°C/W
Thermal resistance 【Junction - Solder point】	$R_{th(j-s)}$	70	°C/W

Note3

Note3  $R_{th(j-a)}$  measurement conditions / Substrate : FR4 (t=1.6mm)  
Pattern size : 16mm<sup>2</sup>

# Specifications

# VXKW1154LCS-TR

## 【Electro-optical characteristics】

Ta=25℃

Item	Symbol	Conditions	Min.	Typ.	Max.	Units	
Forward voltage	$V_F$	$I_F = 30\text{mA}$	2.3	2.9	3.5	V	Note4
Reverse current	$I_R$	$V_R = 5\text{V}$	-	-	10	$\mu\text{A}$	
Luminous intensity	$I_V$	$I_F = 30\text{mA}$	1,200	2,550	3,900	mcd	Note5
Chromaticity coordinates	x	$I_F = 30\text{mA}$	-	0.200	-		Note6,7
	y		-	0.267	-		
Half intensity angle	$\Delta\theta_x$	$I_F = 30\text{mA}$	-	115	-	deg.	Note8
	$\Delta\theta_y$		-	115	-		

Note4 Tolerance:  $\pm 0.1\text{V}$

Note5,6 Please refer to the attached sheets, each sorting chart.

Note7 Chromaticity coordinates ; x and y according to CIE1931

Note8 Viewing Angle at 50%  $I_V$ ,  $\Delta\theta_X$  ; Housing long side axis,  $\Delta\theta_Y$  ; Housing short side axis

## 【Sorting chart for luminous intensity】

LEDs shall be sorted out into the following chart and each rank parts shall be packed separately when shipping.

Rank	Luminous intensity $I_V$ (mcd)		Conditions
	Min.	Max.	
D2	1,200	1,500	$I_F = 30\text{mA}$ $T_a = 25^\circ\text{C}$
D3	1,500	1,800	
D4	1,800	2,200	
D5	2,200	2,700	
D6	2,700	3,300	
D7	3,300	3,900	


Note The above values are the settings of the sorting machine.  
Tolerance:  $\pm 10\%$

Specifications

VXKW1154LCS-TR

【Sorting chart for chromaticity coordinates】

LEDs shall be sorted out into the following chart and each rank parts shall be packed separately when shipping.





$I_F=30\text{mA}$ ,  $T_a=25^\circ\text{C}$

Rank	Left down		Left upper		Right upper		Right down	
	x	y	x	y	x	y	x	y
ZC	0.168	0.219	0.174	0.240	0.191	0.236	0.184	0.214
1C	0.174	0.240	0.180	0.261	0.197	0.257	0.191	0.236
2C	0.180	0.261	0.186	0.282	0.202	0.278	0.197	0.257
3C	0.186	0.282	0.192	0.302	0.208	0.298	0.202	0.278
4C	0.192	0.302	0.198	0.322	0.214	0.318	0.208	0.298
ZD	0.184	0.214	0.191	0.236	0.208	0.231	0.202	0.210
1D	0.191	0.236	0.197	0.257	0.214	0.252	0.208	0.231
2D	0.197	0.257	0.202	0.278	0.219	0.273	0.214	0.252
3D	0.202	0.278	0.208	0.298	0.225	0.294	0.219	0.273
4D	0.208	0.298	0.214	0.318	0.231	0.314	0.225	0.294

Note The above values are the settings of the sorting machine.  
Tolerance:  $\pm 0.01$





Technical Data

VXKW1154LCS-TR







# Technical Data

# VXKW1154LCS-TR



Technical Data

VXKW1154LCS-TR





## Soldering condition


VXKW1154LCS-TR

### 【Soldering Precaution】

(acc.to EIAJ-4701/300)

1. Heat stress during soldering will influence the reliability of LEDs, however that effect will vary on heating method. Also, if components of varying shape are soldered together, it is recommended to set the soldering pad temperature according to the component most vulnerable to heat (e.g., surface mount LED).
2. LED parts including the resin are not stable immediately after soldering ( when they are not at room temperature), any mechanical stress may cause damage to the product. Please avoid such stress after soldering, especially stacking of the boards which may cause the boards to warp and any other types of friction with hard materials.
3. Recommended temperature profile for the reflow soldering is listed as the temperature of the resin surface. Temperature distribution varies on heating method, PCB material, other components in the assembly, and mounting density .  
Please do not repeat the heating process in reflow process more than 2 times.

### 【Recommended Reflow Soldering Condition 】



Note 1 Temperature profile for the reflow should be set to the surface temperature of resin which is on the top of LED. This should be the maximum temperature for soldering. Lowering the heating temperature and decreasing heating time is very effective in achieving higher reliability.

Note 2 The reflow soldering process should be done up to 2 times Max. When second process is performed, interval between first and second process should be as short as possible to prevent absorption of moisture to resin of LED. The second soldering process should not be done until LEDs have returned to room temperature (by nature-cooling) after first soldering process.

## Soldering condition

VXKW1154LCS-TR

4. If soldering manually, the peak temperature changes according to the size of land and the shape of soldering iron tip. Therefore please confirm there is no problem before usage. Also, Stanley recommends using a soldering iron equipped with temperature control and the peak temperature to be lowered.  
During the actual soldering process, make sure that the soldering iron never touches the LED itself, and avoid the LED's electrode temperature reaching above the temperature of the solder pad.  
All repairs must be performed only once in the same spot, and please avoid reusing components.
5. In soldering process, immediately after iron tip is cleaned, please make sure that the soldering iron reaches the appropriate temperature, then use it. Also, please avoid applying any types of pressure to the soldered components before the solder is cooling and hardening, as it may deteriorate solder performance and solder quality.

### 【Recommended manual soldering condition】

Temperature of iron tip	350°C max.
Soldering duration, time	3sec. max., 1 time

6. When using adhesive material for tentative fixatives, thermosetting resin or Ultraviolet radiation(UV) setting resin with heat shall be recommended.  
《Curing condition, Temperature:150°C max. / Time:120sec.max.》
7. Flow soldering (dip soldering) is not guaranteed for this product.
8. Please confirm in advance there is no problem by assessment on your side if cleaning process is necessary.  
We can not accept any quality issues caused by the cleaning process.  
As this product uses the low hardness silicone resin for the lens, please avoid cleaning to give pressure on the surface of the resin.  
Please make sure ultrasonic cleaning is not recommended for this product as well.  
We will recommend isopropyl alcohol as a solvent used for cleaning.  
Some chemicals, including Freon substitute detergent could corrode the lens or the casing surface, which cause discoloration, cloud, crack and so on.  
Please review the reference chart below for cleaning. If water is used to clean (including the final cleaning process), please use pure water (not tap water), and completely dry the component before using.

Cleaning agents	Recommended / Not recommended
Isopropyl Alcohol	✓ Recommended
Trichloroethylene	x Not recommended
Chloroethene	x Not recommended
Acetone	x Not recommended
Thinner	x Not recommended

## Handling precautions

VXKW1154LCS-TR

### 【For electrostatic discharge (ESD)】

LED with an InGaN die is sensitive to voltage surges generated by On/Off status change and friction with synthetic materials, which may cause severe damage to the die or undermine its reliability. Damaged products may experience conditions such as extremely high reverse voltage, decrease of forward rise voltage, deterioration in optical characteristics.

Stanley InGaN products are packed with anti-static components. However, following precautions must be taken into account upon product shipment.

#### 1. Electrification/static electricity protection

In order to avoid product (die) damage from static electricity caused by unprotected handling by operator and other charged materials coming in contact with the product, Stanley recommends taking the following precautions.

- ① Do not place electrified non-conductive materials near the LED product.  
Avoid LED products from coming into contact with metallic materials.( Should the metallic material be electrified , the sudden surge voltage will most likely damage the product.)
- ② Avoid a working process which may cause the LED product to rub against other materials.
- ③ Install ground wires for any equipment, where they can be installed, with measures to avoid static electricity surges.
- ④ Prepare a ESD protective area by placing a Conductive Mattress (1MΩ MAX.) and Ionizer to remove any static electricity.
- ⑤ Operators should wear a protective wrist-strap.
- ⑥ Operators should wear conductive work-clothes and shoes.
- ⑦ To handle the products directly, Stanley recommends the use of ceramic, and not metallic, tweezers.

#### 2. Working environment

- ① A dry environment is more likely to cause static electricity. Although a dry environment is ideal for storage state of LED products, Stanley recommends an environment with approximately 50% humidity after the soldering process.
- ② Recommended static electricity level in the working environment is less than 150V, which is the same value as Integrated Circuits (which are sensitive to static electricity).

## Handling precautions

VXKW1154LCS-TR

### 【Other precautions】


1. Stanley LED Lamps have semiconductor characteristics and are designed to ensure high reliability. However, the performance may vary depending on usage conditions
2. Absolute Maximum Ratings are set to prevent LED lamps from failing due to excess stress( temperature, current, voltage, etc.). Usage conditions must not exceed the ratings for a moment, nor do reach one item of absolute maximum ratings simultaneously.
3. In order to ensure high reliability from LED Lamps, variable factors that arise in actual usage conditions should be taken into account for designing. ( Derating of TYP., MAX Forward Voltage, etc.)
4. Please insert Protective Resistors into the circuit in order to stabilize LED operation and to prevent the device from igniting due to excess current.
5. Please avoid the stick of foreign material because molding resin in the products have adhesiveness. Also please don't touch lens portion.
6. Please check the actual performance in the assembly because the Specification Sheets are described for LED device only.
7. Please refrain from looking directly at the light source of LED at high output, as it may harm your vision.
8. The products are designed to operate without failure in recommended usage conditions. However, please take the necessary precautions to prevent fire, injury, and other damages should any malfunction or failure arise.
9. The products are manufactured to be used for ordinary electronic equipment. Please contact our sales staff beforehand when exceptional quality and reliability are required, and the failure or malfunction of the products might directly jeopardize life or health ( such as for airplanes, aerospace, transport equipment, medical applications, nuclear reactor control systems and so on).
10. When there is a process of supersonic wave welding etc. after mounting the product, there is a possibility of affecting on the reliability of junction part in package (junction part of die bonding and wire bonding). Please make sure there is no problem before using.
11. The formal specification sheets shall be valid only by exchange of documents signed by both parties.

## Handling precautions


VXKW1154LCS-TR

### 【Handling precautions for product mounting】

#### <Recommendation>

1. Picking up point with nozzle : Lamp housing of the product (  area : Shown below)


The pick up point is lamp housing only because the silicone resin used for the lens is soft.  
(If the nozzle makes contact with the lens, the products might be destroyed)




Please adjust the load, the pick up point, the nozzle diameter and etc. before mounting because the over load can cause the breakage of the lamp housing.

2. Recommended nozzle shape

a



b



※ Nozzle with chamfering is recommended

## Packaging specifications

VXKW1154LCS-TR

This product is baked (moisture removal) before packaging, and is shipped in moisture-proof packaging (as shown below) to minimize moisture absorption during transportation and storage. However, with regard to storing the products, Stanley recommends the use of dry-box under the following conditions is recommended. Moisture-proof bag as the packaging is made of anti-static material but packaging box is not.

### 【Recommended storage condition / products warranty period】

Temperature	+5~30°C
Humidity	Under 70%

In the case of the package unopened , please use within **6 months** **【Recommended storage condition】**. Please avoid rapid transition from low temp. condition to high temp. condition and storage in corroding and dusty environment.

### 【Time elapsed after package opening】

The package should not be opened until immediately prior to its use, and please keep the time frame between package opening and soldering which is **【maximum 672h】**.

If the device needs to be soldered twice, both soldering operations must be completed within the 72h.

If any components should remain unused, please reseal the package and store them under the conditions described in the **【 Recommended Storage Condition 】** above.

This product must be required to perform baking process (moisture removal) for **at 48h (min.) to 72h (max.) at 60±5 degrees Celsius** if following conditions apply.

1. In the case of silica gel (blue) which indicates the moisture level within the package, changes or loses its blue color.
2. In the case of time passes for 672h after the package is opened once.


Baking process should be performed after LED having been taken out of the package.

Baking may be performed in the tape-reel form , however if it is performed with the reel stacked over one another, it may cause deformation of the reels and taping materials and later obstruct mounting. Please handle only once it has returned to room temperature. Provided that, baking process shall be 2 times max.

Packaging specifications


VXKW1154LCS-TR

【Moisture-proof packaging specification】



No.	Part name	Material	Remarks
①	Moisture-proof bag with Aluminum layer	PET+Al+PE	with ESD protection

【Flow chart-package opening to mounting】



Allowable leaving time means the maximum allowable leaving time after opening package, which depends on each LED type. The allowable leaving time should be calculated from the first opening of package to the time when soldering process is finished. When judging if the allowable leaving time has exceeded or not, please subtract the soldering time. The allowable leaving time after reopening should be calculated from the first opening of package, or from the time when baking process is finished.

Packaging specifications


VXKW1154LCS-TR

【Packing box】

( RoHS2 / ELV Compliant )

Box type	Outline dimension L × W × H (mm)	Capacity of the box
Type A	280 x 265 x 45	3 reels
Type B	310 x 235 x 265	15 reels
Type C	440 x 310 x 265	30 reels

The above measure is all the reference value.  
The box is selected out of the above table by shipping quantity.



Type A  
Material / box : Cardboard C5BF

Type B,C  
Material / box : Cardboard K5AF  
Partition : Cardboard K5BF

No.	Part name	Material	Remarks
②	Packing box	Corrugated cardboard	without ESD protection



Packaging specifications

VXKW1154LCS-TR

(acc.to JIS-X0503(Code-39))

【Label specification】

A Product label

STANLEY-STANLEY ELECTRIC CO.,LTD.-

A

B

( C )

D PCS

E

Lot No. F

G

- A. Parts number
- B. Bar-code for parts number
- C. Parts code (In-house identification code for each parts number)
- D. Packed parts quantity
- E. Bar-Code for packed parts quantity
- F. Lot number & rank
- (Please refer to lot number notational system for details )
- G. Bar-code for lot number & rank

B Opto device label

STANLEY OPTO DEVICES

A

御中

B

D

( C )

Q'TY E PCS G

C/NO F

H

STANLEY ELECTRIC CO.,LTD.

- A. Customer name
- B. Parts type
- C. Parts code
- D. Parts number
- E. Packed parts quantity
- F. Carton number
- G. Shipping date
- H. Bar-code for In-house identification number


<Remarks> Bar-code font : acc.to Code-39(JIS-X0503)

## Taping and reel specifications

VXKW1154LCS-TR

(acc.to JIS-C0806-03)

## 【Appearance】



## Note

"-TR" means Cathode Side of LEDs; should be placed on the sprocket-hole side.

Items		Specifications	Remarks
Leader area	Cover-tape	Cover-tape shall be longer than <b>300mm</b> without carrier-tape	The end of cover-tape shall be held with adhesive tape.
	Carrier-tape	Empty pocket shall be more than <b>25 pieces</b> .	Please refer to the above figure for Taping & reel orientation .
Trailer area		Empty pocket shall be more than <b>40 pieces</b> .	The end of taping shall be inserted into a slit of the hub.

## Taping and reel specifications

VXKW1154LCS-TR

(acc.to JIS-C0806-03)

## 【 Qty. per reel】

2,000parts/reel

Minimum Qty. per reel might be 500 parts when getting less than 3,000 parts.

In such case, parts of 500-unit-qty. shall be packed in a reel and the qty. shall be identified on the label

## 【Mechanical strength】

Cover-tape adhesive strength shall be 0.1 ~ 1.0N ( An angle between carrier-tape and cover-tape shall be 170 deg. ).

Both tapes shall be so sealed that the contained parts will not come out from the tape when it is bent at a radius of 15mm.

## 【 Others】

Reversed-orientation, Up-side down placing, side placing and out of spec. parts mix shall not be held.

Empty pocket per reel shall be defined as follows.

Qty./reel	Max. qty. of empty pocket	Remarks
500	1	-
1,000	1	-
1,500	1	-
2,000	2	No continuance

## VXKW1154LCS-TR

Unit: mm

Technical drawing of a mechanical part, showing front and side views with dimensions and feature labels.

**Front View Dimensions:**

- Top hole diameter:  $\Phi 1.5^{+0.1}_0$
- Top hole center-to-center distance:  $4 \pm 0.1$
- Top hole diameter (alternative): (3.25)
- Top hole diameter (alternative): 3
- Top hole diameter (alternative):  $1.75 \pm 0.2$
- Bottom hole diameter:  $\Phi 1.0 \pm 0.2$
- Bottom hole center-to-center distance: (3.5)
- Bottom hole diameter (alternative): 8  $\pm 0.2$
- Bottom hole diameter (alternative): (2)
- Bottom hole diameter (alternative): (4)

**Side View Dimensions:**

- Top hole diameter: (0.2)
- Top hole diameter (alternative): ①
- Bottom hole diameter: (3.7)
- Bottom hole diameter (alternative): ②
- Bottom hole diameter (alternative): (2.3)

**Feature Labels:**

- Center Hole

No.	Part name	Remarks
①	Carrier-tape	with ESD protection
②	Cover-tape	with ESD protection
③	Carrier-reel	with ESD protection

## Lot number notational system

VXKW1154LCS-TR

①	②	③	④	⑤	⑥	⑦	⑧	⑨							

① - 1digit : Production location (mark identify alphabet)

② - 1digit : Production year (The last digit of production year 2024→4, 2025→5, 2026→6, 2027→7 ...)

③ - 2digits : Production month (Jan. to Sep. , should be 01,02,03 ...)

④ - 2digits : Production date

⑤ - 3digits : Serial number

⑥ - 2digits : Tape and reel following number

⑦ - 2digits : Luminous intensity rank.

(If luminous intensity rank is 1 digit, "-" shall be dashed on the place for the second digit.

If there is no identified rank, "- -" is used to indicate.)

⑧ - 2digits : Chromaticity coordinates rank

(If chromaticity coordinates rank is 1 digit, "-" shall be dashed on the place for the second digit.

If there is no identified rank, "- -" is used to indicate.)

⑨ - 1digit : VF Rank (If rank is not defined, "-" is described.)

## Compliance with RoHS2/ELV

VXKW1154LCS-TR

This product is in compliance with RoHS2 / ELV.

Prohibition substance and it's criteria value of RoHS2 / ELV are as follows.

- RoHS2 instruction ... Refer to following 1 to 10.
- ELV instruction ... Refer to following 1 to 4.

No.	Substances	Threshold
1	Lead and its compounds	0.1% (1,000ppm)
2	Mercury and its compounds	0.1% (1,000ppm)
3	Cadmium and its compounds	0.01% (100ppm)
4	Hexavalent chromium compounds	0.1% (1,000ppm)
5	PBB : Polybrominated Biphenyls	0.1% (1,000ppm)
6	PBDE : Polybrominated Biphenyl Ethers	0.1% (1,000ppm)
7	DEHP : Bis (2-ethylhexyl) phthalate	0.1% (1,000ppm)
8	BBP : Butyl benzyl phthalate	0.1% (1,000ppm)
9	DBP : Dibutyl phthalate	0.1% (1,000ppm)
10	DIBP : Diisobutyl phthalate	0.1% (1,000ppm)

# Reliability Testing Result

# VXKW1154LCS-TR

## 1. Reliability testing result

Test item	Standard	Test condition	Duration	Failure
Room temperature operating life	EIAJ ED-4701 / 100(101)	Ta=25°C I <sub>F</sub> =40mA	1,000h	0 / 20
High temperature operating life	EIAJ ED-4701 / 100(101)	Ta=85°C I <sub>F</sub> =40mA	1,000h	0 / 20
Low temperature operating life	EIAJ ED-4701 / 100(101)	Ta=-40°C I <sub>F</sub> =40mA	1,000h	0 / 20
Wet high temperature operating life	EIAJ ED-4701 / 100(102)	Ta=60°C Rh=90% I <sub>F</sub> =40mA	1,000h	0 / 20
High wet - high temp. operating life	EIAJ ED-4701 / 100(102)	Ta=85°C Rh=85% I <sub>F</sub> =40mA	1,000h	0 / 20
High temperature storage life	EIAJ ED-4701 / 200(201)	Ta=120°C	1,000h	0 / 20
Low temperature storage life	EIAJ ED-4701 / 200(202)	Ta=-40°C	1,000h	0 / 20
Wet high temperature storage life	EIAJ ED-4701 / 100(101)	Ta=60°C Rh=90%	1,000h	0 / 20
Thermal shock	EIAJ ED-4701 / 100(105)	Ta=-40°C to 110°C (each 15min)	1,000 cycles	0 / 20
Thermal shock operating	EIAJ ED-4701 / 100(105)	Ta=-40°C(OFF) to 85°C(I <sub>F</sub> =40mA ON) (each 15min)	1,000 cycles	0 / 20
Resistance to reflow soldering	EIAJ ED-4701 / 300(301)	Moisture Soak : 60°C 60% 120h Preheating : 150 to 180°C 90-120sec Soldering : 260°C peak	2 times	0 / 20
Electrostatic discharge (ESD)	EIAJ ED-4701 / 300(304)	C=100pF R2=1.5kΩ ±1,000V	3 times of each polarity	0 / 20
Vibration, variable frequency	EIAJ ED-4701 / 400(403)	98.1m / s <sup>2</sup> (10G) 100 to 2,000Hz 20min sweep XYZ directions	2h of each direction	0 / 20

## 2. Failure criteria

Item	Symbol	Condition	Failure criteria
Luminous intensity	I <sub>V</sub>	I <sub>F</sub> =30mA	Testing Min. Value < Standard Min. Value × 0.5
Forward voltage	V <sub>F</sub>	I <sub>F</sub> =30mA	Testing Max. Value ≥ Standard Max. Value × 1.2
Cosmetic appearance	-	-	Notable discoloration, deformation and cracking

VXKW1154LCS-TR

## Special Notice to Customers Using the Products and Technical Information Shown in This Data Sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products that have been described to this catalog are manufactured so that they will be used for the electrical instrument of the benchmark (OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument).  
The application of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. needs a high reliability and safety, and the breakdown and the wrong operation might influence the life or the human body. Please consult us beforehand if you plan to use our product for the usages of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. except OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument.
- 5) In order to export the products or technologies described in this data sheet which are under the "Foreign Exchange and Foreign Trade Control Law," it is necessary to first obtain an export permit from the Japanese government.
- 6) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 7) The most updated edition of this data sheet can be obtained from the address below:  
<http://www.stanley-components.com/en/>